

AIR TOOLS

Paving Breakers, Hammers, Busters, Diggers, Tampers, Rock Drills, Post Drivers, and Nailers



PAVING BREAKERS



APT/M117

- Light duty concrete breaker
- Patent ball valve design and built-in automatic oiler make this breaker low maintenance



APT/M160

- Medium to heavy demolition work and concrete breaking
- Rubber handle grips for comfort
- Built in automatic oiler



APT/M190

- Designed for heavy demolition and concrete breaking
- Ideal for road building and foundation removal
- Built in automatic oiler

MAKE	MODEL	SHANK SIZE	STROKE	BPM	CFM	WEIGHT	AIR INLET NPT	CAT-CLASS
APT	117	1 X 4-1/4"	3-3/8"	1,850	34-48 @ 90 PSI	33 lbs	3/8 Male	120-1610
APT	160	1-1/8 x 6"	4-1/8"	1,680	60-65 @ 90 PSI	68 lbs	1/2 Male	120-1640
APT	190	1-1/8 x 6"	6-1/8"	1,350	75-80 @ 90 PSI	91 lbs	3/4 Male	120-1660

HAMMERS



APT/CHIPPING HAMMER 264H/18671

- Light concrete demolition

BUSTERS



APT/M133CN/18768

- Medium to heavy demolition work
- Meets the weight requirements for bridge deck

DIGGERS



APT/CLAY DIGGER M118/5201

- Clearing out dirt under existing foundations
- Horizontal and vertical work

MAKE	MODEL	TYPE	HANDLE	SHANK SIZE	STROKE	BPM	CFM	WEIGHT	AIR INLET NPT	CAT-CLASS
APT	264	Hammer	D-Handle	.580 Hex	4"	1375	34-36 @ 90 PSI	15 lbs	7/8-24	120-1520
APT	M133CN/18768	Busters	D-Handle	11 x	8"	1140	42-46 @ 90 PSI	30 lbs	1/2 Female	120-2030
APT	118	Digger	D-Handle	7/8 x 3-1/4 in	3-3/8"	1850	34-36 @ 90 PSI	31 lbs	3/8 Male	120-1700

TAMPERS



APT/BACKFILL TAMPER M131/5214

- Soil compaction, temporary filling of holes, and asphalt packing
- Foundation and pavement repair
- Installation of power or telephone poles



Three styles of butts available:
3 and 6 inch diameter, half moon

AIR MANIFOLD



TX/TX-2AMF

- Use when there is a need to have multiple outlets of air to supply various pneumatic tools simultaneously
- Drain valve on bottom of tank
- Units can be linked together by replacing the square plug with a hose coupling

MAKE	MODEL	CHUCK/BUTT SIZE	STROKE	BPM	CFM	WEIGHT	AIR INLET NPT	CAT-CLASS
APT	131	6" Round	5-1/2"	670	38-42 @ 90 PSI	37 lbs	1/2 Female	150-1720

MAKE	MODEL	TANK CAPACITY	INLET	OUTLETS	WORKING PRESSURE	WEIGHT	CAT-CLASS
Texas Pneumatic	TX-2AMF	15 Gallon (ASME)	(1) 2in 4-Prong Coupling	(8) 3/4 in Ball Valves w/ Crows Ft Couplings	200 psi	63 lbs	140-3580
Texas Pneumatic	TX-4AMF	30 Gallon (ASME)	(1) 2in 4-Prong Coupling	(8) 3/4 in Ball Valves w/ Crows Ft Couplings	200 psi	115 lbs	

ROCK DRILLS



APT/M115

- Lightweight for drilling holes for anchor bolts
- Converts from a drilling tool to a percussion tool
- Built-in automatic oiler



APT/M137

- Granite, hard-faced rock, quarry drilling
- Adaptable wet drilling application



APT/M155

- Granite, hard-faced rock, quarry drilling
- Adaptable wet drilling application

MAKE	MODEL	SHANK SIZE	STROKE	BPM	CFM	WEIGHT	AIR INLET NPT	CAT-CLASS
APT	115	7/8" X 3-1/4"	1-3/8"	2,900	32-36 @ 90 PSI	19 lbs	3/8 Male	120-1760
APT	137	7/8" X 3-1/4"	2-5/8"	2,300	85-90 @ 90 PSI	38 lbs	1/2 Male	120-1780
APT	155	7/8" X 3-1/4"	3"	2,100	110-120 @ 90 PSI	61 lbs	3/4 Male	120-1820

POST DRIVERS



RHINO/PD-55

- Transport kit with PD-55
- Includes air hose, throttle kit, and filter regulator

RHINO/CART KITS

- Air kit includes PD55, F.R.L., and 4 most common adapters
- Gas kit includes Multi-Pro XA, and 1", 1 1/4", 2" adapters

RHINO/MULTI-PRO XA (Included in Kit)

- Gas powered post driver for installing a wide range of post profiles and sizes
- Comfort handling
- Easy to use, quick change adapters

MAKE	MODEL	CHUCK/BUTT SIZE	CFM @ 90 PSI	WEIGHT	CAT-CLASS
Rhino	PD-55	3-7/8"	42	54.6 lbs	115-2600
Rhino	MULTI-PRO XA	2-1/2"	Gas	44 lbs	115-2610

NAILERS



BOSTITCH/N80CB-1ML

- Easy to use, coil frame nailer
- Contact-trip trigger; large-capacity magazine
- Aluminum housing
- Accommodates nails from 1-1/2" to 3-1/4"

BOSTITCH/FN1664K

- Oil-free engine
- Selectable trigger system
- Trigger lockout mode for use when working in occupied spaces
- Dial-A-Depth control

BOSTITCH/BTFP12569

- Popular floor nailer
- 2-in-1 tool drives staples and L-shaped cleat nails

MAKE	MODEL	FASTENER SIZE	FASTENER	MAGAZINE CAPACITY	FITTING	PSI	WEIGHT	CAT-CLASS
Bostitch	F28WW	2 - 3 1/2"	Framing nailer	100	3/8 Quick connect	80-120	7.6 lbs	100-5620
Bostitch	N80CB-1ML	1 1/2 - 3 1/4"	Coil Framing	300	Coil Load	70-100	8.5 lbs	100-5620
Bostitch	FN1664K	1 1/4 - 2 1/2"	Finishing	100	Bottom Load	70-120	3.9 lbs	100-5630
Bostitch	BTFP12569	1 1/2 - 2"	Staples	100	Locked Load	70-120	2.9 lbs	100-5210

AIR DRILLS



IR/1PT38ST4

- Compact and light weight
- Variable speed control
- Contoured rear radius provides comfortable, convenient position for gripping.



CS UNITEC/22404001

- Safety clutch for overloading and jamming
- Hammer drill holes in concrete, brick + masonry
- Straight drilling of steel and wood



CS UNITEC/MAB 525

- Powerful and reliable
- Quick-change keyless cutter system
- Integrated cutting oil reservoir

MAKE	MODEL	TYPE	SIZE	CFM @ 90PSI	RPM	CAT-CLASS
Cleco	15DP	Horizontal	1/2"	15	160 rpm	120-3500
IR	728LA2	Horizontal	3/8"	3.20	3,800 rpm	120-3510
CS Unitec	22404001	Rotary	3"	31	0-625 rpm	100-1180
CS Unitec	MAB 525	Magnetic	2" - 2-1/2"	-	580 rpm	130-1250
CS Unitec	ECO80AK	Magnetic	3"	-	4 speed	130-1260

AIR GRINDERS



IR/HD180RG4

- Ideal for heavy duty stock removal
- Vibration dampening handle
- Superior power to weight ratio



IR/HA120RP1045

- Industrial duty material removal with burrs grinding wheels and coated abrasives
- Powerful vane motor
- Optimized for general industrial use



IR/88V60P

- Solid steel motor and arbor housing
- Built-in mist lubricator automatically oils motor
- Heavy-duty, double-row ball bearings

MAKE	MODEL	TYPE	DIAMETER	ARBOR	FREE SPEED	WEIGHT	CAT-CLASS
IR	HD180RG4	7" Batwing	1/4" collet	3/8"	600 rpm	8.75 lbs	120-3050
IR	HA120RP1045	4" Right angle	1/4" collet	3/8"	12,000 rpm	3.6 lbs	120-3010
IR	88V60P	Horizontal	1/4" collet	3/8"	6,500 rpm	8.75 lbs	120-3020

AIR IMPACT WRENCHES



IR/2925Ti

- Titanium hammer case
- Pressure fed lubrication mechanism
- Twin hammer mechanism



IR/3955B1Ti

- Titanium hammer case
- Twin hammer mechanism
- 7-vane reverse-bias motor

MAKE	MODEL	DRIVE	MAX TORQUE	SPEED	WEIGHT	CAT-CLASS
Cleco	9525	3/8"	510	8,000 rpm	2.9 lbs	135-2560
IR	MP-1700	1/2"	370	6,500 rpm	5.3 lbs	135-2580
IR	2925Ti	3/4"	1,450	5,200 rpm	12 lbs	135-2590
IR	2925B2Ti	1"	1,600	6,500 rpm	15.20 lbs	135-2600
IR	3955B2Ti	1-1/2"	5,000	295 rpm	36.5 lbs	135-2610
IR	3955B1Ti	1-1/2" Spline	5,000	2,750 rpm	34.6 lbs	135-2620

AIR SAWS



IR/S80

- Faster removal and tightening of large fasteners
- Precision ball and cam impact mechanism
- Portable, easy to handle or suspend



IR/SRA010A1

- Titanium hammer case
- Pressure fed lubrication mechanism
- Twin hammer mechanism



CS UNITEC/5 1212 0010

- Titanium hammer case
- Twin hammer mechanism
- 7-vane reverse-bias motor

MAKE	MODEL	TYPE	BLADE SIZE	CFM @ 90PSI	CAT-CLASS
IR	S80	Circular	8-1/4"	67	120-3600
IR	SRA010A1	Reciprocating	2-3/8"	51	120-3610
CS Unitec	5 1212 0010	Hack saw	2-3/8"	51	120-3620
CS Unitec	5 6003 0010	Portable Band	44-7/8" x 1/2"	21	120-3630

AIR POWERED FANS



COPPUS/Vano 175 CV

- Accepts ducting at inlet and outlet ends
- Ideal for ventilating confined spaces
- High Volume - High Static pressure



TX-PNEU/TX-6-AM

- Used for venting hazardous areas
- Operates on compressed air or steam
- Can be used as a blower or exhauster



TX-PNEU/TX-JF12 JETFAN

- Ventilation of tanks, process vessels, or other confined areas
- Use as blower or exhauster
- 4" blade design produces high airflow at lower RPM

MAKE	MODEL	AIRFLOW	INSIDE DIAMETER	DIMENSIONS (LWH)	WEIGHT	CAT-CLASS
COPPUS	175 CV	1,500 CFM	8 in	39" x 11.4" x 13.8"	73 lbs	700-1220
Texas Pneumatic	TX-3-AM	60 PSIG - 863 CFM / 80 PSIG - 1067 CFM / 100 PSIG - 3698 CFM	3 in	32" x 7.3" x 7"	10 lbs	710-1220
Texas Pneumatic	TX-6-AM	60 PSIG - 2560 CFM / 80 PSIG - 3020 CFM / 100 PSIG - 3698 CFM	6 in	44" X 11.2" X 12.5"	25 lbs	710-1240
Texas Pneumatic	TX-8-AM	60 PSIG - 2560 CFM / 80 PSIG - 3020 CFM / 100 PSIG - 3698 CFM	8 in	46.5" x 14.3" x 14.3"	36 lbs	710-1260
Texas Pneumatic	TX-10-AM	4898@40CFM, 6182@60CFM, 7304@80CFM	10 in	48" x 16.8" x 15.8"	43 lbs	710-1280
Texas Pneumatic	TX-JF12	60 PSIG - 2,161 CFM / 80 PSIG 2,550 CFM / 100 PSIG 2,866 CFM	12 in	11" x 12.3" Diameter	41 lbs	710-1300
Texas Pneumatic	TX-JF20	60 PSIG - 7,600 CFM / 80 PSIG 9,100 CFM / 100 PSIG 10,420 CFM	20 in	12" x 24.5" Diameter	96 lbs	710-1360
Texas Pneumatic	TX-JF24	60 PSIG - 11,005 CFM / 80 PSIG 12,848 CFM / 100 PSIG 16,136 CFM	24 in	12" x 31.3" Diameter	131 lbs	710-1320

MOBILE TOOL ROOM



MOBILE TOOL ROOM /

Provides an easy and functional way to manage numerous tools on location. Allow Herc Rentals professionals to assist you in our tool management system for your next project.

