

# PORTABLE POWER

Generators, Generator Performance  
and Information Guide



PORTABLE POWER



**GENERATORS**



HONDA/EU2200iTA1

- Clean inverter power at 53 to 59 dBA
- Rated at 2 kW
- Ideal for TV/DVD, satellite, fridge, computers



HONDA/EB3000CK2A

- Lightweight portable generator
- Rated at 3 kW
- Up to 9.4 hours of run time



HONDA/EU3000iS1A

- Super quiet 49 to 58 dB(A)
- Rated at 3 kW
- Ideal for furnace, fridge, microwave, and RV AC units



HONDA/EB5000XK3

- Mobile job site generator
- Rated at 5 kW
- 7kW max output for 10 seconds



HONDA/EU7000iAT1

- Operates at 52 to 60 dBA
- Rated at 7 kW
- Inverter - perfect for home back up power, RVs, outdoor events



HONDA/EB10000

- 10kw commercial generator
- Rated at 10 kW
- 2 wheel kit and lift hook

MAKE	MODEL	TYPE	RATED WATTS	SURGE WATTS	VOLTAGE/AMPS	FUEL CAPACITY	RUN TIME	WEIGHT	CAT-CLASS
Honda	EU2200iTA1	Inverter Generator	1,600 W	2,000 W	120v / 16.7A	0.9 Gallons	4.0 hrs	46 lbs	500-1025
Honda	EB3000CK2A	Portable Generator	2,600 W	3,000 W	120v / 25A	2.6 Gallons	6.1 hrs	71 lbs	500-1030
Honda	EU3000iS1A	Portable Inverter Generator	2,800 W	3,000 W	120v / 25A	3.4 Gallons	7.2 hrs	134 lbs	500-1035
Honda	EB5000XK3	Portable Generator	4,001 W	6,000 W	120-240v	6.2 Gallons	8.1 hrs	214 lbs	500-1050
Honda	EU7000iAT1	Inverter Generator	5,500 W	7,000 W	120-240v / 58.3-29.1A	5.1 Gallons	6.5 hrs	262 lbs	500-1075
Honda	EB10000	Portable Generator	9,000 W	10,000 W	120-240v / 83.8-41.6A	8.1 Gallons	5.3 hrs	403 lbs	500-1100

# PORTABLE BATTERY POWER SOLUTIONS



GRIDLESS/1000

- Stop running loud generators and long runs of cable
- Great for charging phones and powering LED lighting in areas lacking nearby shore power
- Drop, shock and weather resistant case



GRIDLESS/7000

- Clean power is ideal for DJs and live bands
- Solid rubber tire running gear allows for positioning close to equipment
- Charge from wall, solar panel or vehicle

MAKE	MODEL	CAPACITY	OUTPUTS	RUN TIME	CHARGING TIME	RUN TIME @ 15AMP DRAW	WEIGHT	CAT-CLASS
Gridless	1000	1kW Continuous, 2kW Surge AC	(4) AC Outlets, (8) USB	3 Hours @ 3 Amps	1 to 4 hours	3 Hours @ 3 Amps	50 lbs	502-1010
Gridless	7000	5kW Continuous, 10kW Surge AC	(8) AC Outlets, (2) Twist Lock, (8) USB	4.5 Hours @ 15 Amps	4 to 7 hours	4.5 Hours @ 15 Amps	350 lbs	502-1070



# GENERATORS



### MULTIQUIP/DCA70SSIU4F

- Super-silent portable generator
- Rated at 56kW
- Towable

### MULTIQUIP/DCA300SSJU4F2

- Galvanized skid-mounted for reduced footprint
- Super-silent generator-72dBa
- 3-way fuel valve enabling external fuel source hookup for longer runs

### CUMMINS/ C500D6RG

- Provides more than 24 hours runtime on a single tank at full load
- Paralleling system to connect multiple units
- Tier 2 diesel engine for continuous power without having to re-gen

MODEL	TIER	KW PRIME (STANDBY)	STYLE	DIMENSIONS IN INCHES (LWH)	DRY WEIGHT	WET WEIGHT	TOTAL FUEL CAPACITY	FUEL CONSUMPTION (FULL LOAD)	RUNTIME	CAT CLASS
DCA25SSIU4F	4F	20 (22)	Trailer	105" x 57" x 62"	2,365 lbs	2,705 lbs	42 gal	1.62GPH	25 hrs	501-1020
DCA45SSIU4F	4F	36 (40)	Trailer	148" x 66" x 77"	3,395 lbs	4,035 lbs	79 gal	2.93GPH	27 hrs	501-1040
DCA70SSJU4i	4i	56 (62)	Trailer	166" x 72" x 85"	4,683 lbs	5,414 lbs	103 gal	4.30 GPH	23 hrs	501-1055
DCA70SSIU4F	4F	56 (62)	Trailer	166" x 72" x 85"	4,420 lbs	5,300 lbs	103 gal	4.40 GPH	23 hrs	501-1055
DCA125SSJU4i	4i	100 (110)	Trailer	182" x 80" x 90"	6,856 lbs	8,049 lbs	168 gal	7.30 GPH	23 hrs	501-1100
DCA125SSIU4F	4F	100 (110)	Trailer	181" x 79" x 120"	7,010 lbs	8,210 lbs	169 gal	7.11 GPH	23 hrs	501-1100
			Skid	138" x 56" x 96"	6,065 lbs	7,475 lbs	169 gal	7.11 GPH	23 hrs	501-1105
DCA150SSJU4F	4F	120 (132)	Trailer	209" x 85" x 96"	9,195 lbs	11,176 lbs	279 gal	8.40 GPH	33 hrs	501-1120
DCA220SSJU4F	4F	176 (194)	Trailer	210" x 88" x 99"	10,456 lbs	13,076 lbs	369 gal	12.50 GPH	29 hrs	501-1175
			Skid	153" x 59" x 96"	8,570 lbs	9,365 lbs	69 gal	12.50 GPH	5 hrs	501-1180
DCA300SSJU4F	4F	240 (264)	Trailer	223" x 95" x 106"	13,418 lbs	16,258 lbs	400 gal	17.20 GPH	23 hrs	501-1250
			Skid	167" x 67" x 86"	12,335 lbs	13,045 lbs	100 gal	17.20 GPH	5 hrs	501-1255
DCA300SSJU4F2	4F	240 (264)	Trailer	224" x 100" x 120"	14,296 lbs	17,353 lbs	431 gal	16.70 GPH	25 hrs	501-1250
			Skid	167" x 67" x 108"	12,335 lbs	16,125 lbs	431 gal	16.70 GPH	25 hrs	501-1255
DCA400SS14F	4F	320 (336)	Trailer	265" x 94" x 111"	16,560 lbs	19,439 lbs	406 gal	22.50 GPH	18 hrs	501-1320
			Skid	193" x 67" x 106"	13,450 lbs	14,355 lbs	56 gal	22.50 GPH	2 hrs	501-1325
C500D6RG	TIER 2	455 (500)	Trailer	239" x 96" x 148"	29,440 lbs	35,380 lbs	849 gal	30.4 GPH	27 hrs	501-1500
C1000D6RG	TIER 2	900 (1000)	Trailer	359" x 96" x 160"	41,280 lbs	53,378 lbs	1704 gal	63.9 GPH	26 hrs	501-2100

# GENERATOR PERFORMANCE CHART

PRIME POWER OUTPUT RATING	AMPS AT 3-PHASE 0.8 PF		AMPS AT 1-PHASE 1.0 PF	
	240V	480V	4-WIRE*	240/120V ZIG ZAG

MODEL	KVA	KW	240V	480V	120V	240V	120V	240V	MAIN LINE CB RATING AMPS	OCR** TRIP SET AMPS	MSKVA @ 30 % VDIP
DCA25SSIU4F	25	20	60	30	56 x 3	28 x 3	60 x 2	60	60	30	65
DCA45SSIU4F	45	36	108	54	100 x 3	50 x 3	108 x 2	108	125	54	100
DCA70SSIU4F	70	56	168	84	155 x 3	78 x 3	168 x 2	168	175	84	170
DCA125SSIU4F	125	100	300	150	278 x 3	139 x 3	301 x 2	301	300	152	410
DCA150SSJU4F	150	120	361	180	333 x 3	167 x 3	361 x 2	361	400	180	500
DCA220SSJU4F	220	176	529	265	488 x 3	244 x 3	N/A	N/A	600	265	700
DCA300SSJU4F	300	240	722	361	666 x 6	333 x 3	N/A	N/A	800	361	800
DCA400SSI4F	400	320	962	481	888 x 3	444 x 3	N/A	N/A	1000	481	1000



PORTABLE POWER