

PUMPS

Submersible Pumps and Trash Pumps



SUBMERSIBLE



WACKER NEUSON / **PST2 400**

- Lightweight, compact submersible pump with built-in thermal protection
 - Shaft-mounted agitators to suspend solids
- 53 GPM with 2" discharge



WACKER NEUSON / **PS2 500**

- Lightweight, compact submersible pump
 - Shaft-mounted agitators to suspend solids
- 62-1/3 GPM with 2" discharge



WACKER NEUSON / **PST3 750**

- Lightweight, compact submersible pump
 - Shaft-mounted agitators to suspend solids
- 60 GPM with 3" discharge

MAKE	MODEL	OUTLET SIZE	MAX GPM	MAX HEAD	HP/VOLTAGE	DEBRIS SIZE	WEIGHT	CAT-CLASS
Wacker Neuson	PST2 400	2"	62.3 gpm	39.5'	110v	.2"	21 lbs	809-1860
Wacker Neuson	PS2 500	2"	53 gpm	39'	110v	.27"	21 lbs	809-1860
Wacker Neuson	PST3 750	3"	60 gpm	62'	110v	.27"	42 lbs	809-1880

TRASH PUMPS



WACKER NEUSON / **PT3A**

- Self-priming, centrifugal trash pump with high gpm capability
- Popular for general dewatering of excavations, flooded basements, manholes
- Can handle solids up to 1.5"



MULTIQUIP / **QP4TH**

- Industrial centrifugal trash pump for the toughest dewatering applications
- Large clean-out chamber
- Moves up to 2" solids

DIAPHRAGM PUMP



MULTIQUIP / **PDT3A**

- Diaphragm design is ideal for moving water with mud and debris
- Handles solids up to 1.6"
- Solid rubber tires for smooth rolling over rough terrain

MAKE	MODEL	SUCTION X DISCHARGE	MAX GPM	MAX HEAD	FUEL / CAPACITY	RUN TIME	DIMENSIONS (LWH)	WEIGHT	CAT-CLASS
Wacker Neuson	PT2A	2 x 2"	172 gpm	106'	Gasoline / 0.83 Gal	2 hrs	21.7" x 18.3" x 19.6"	92 lbs	800-1080
Wacker Neuson	PT3A	3 x 3"	356 gpm	93'	Gasoline / 1.30 Gal	2.5 hrs	26.5" x 20" x 22.5"	150 lbs	800-1090
Multiquip	QP4TH	4 x 4"	555 gpm	90'	Gasoline / 1.65 Gal	1.5 hrs	30.1" x 27.3" x 30.7"	216 lbs	800-1110

MAKE	MODEL	SUCTION X DISCHARGE	MAX GPM	MAX HEAD	FUEL / CAPACITY	RUN TIME	DIMENSIONS (LWH)	WEIGHT	CAT-CLASS
Wacker Neuson	PDT3A	3 x 3"	88 gpm	25'	Gasoline / 2.6	2.2 hrs	33" x 32" x 31.5"	140 lbs	800-1130