

DRYING + REMEDIATION



DRYING + REMEDIATION



DEHUMIDIFIERS

LGR



DRI-EAZ/REVOLUTION LGR

- Removes 8 gallons per day
- Can be stacked to double footprint
- Displays temperature and RH in real time



DRI-EAZ/7000XLI

- Removes 16 gallons per day
- Self-monitoring system
- Built-in humidistat

MAKE	MODEL	MOISTURE REMOVAL (MAX)	MOISTURE REMOVAL (AT AHAM)	CFM RATING	AMP RATING	DIMENSIONS (LWH)	WEIGHT	CAT-CLASS
Dri-Eaz	Revolution LGR	10.1 Gal/Day	8 Gal/Day	121-180	6.2	22" x 18" x 13"	65 lbs	719-2020
Dri-Eaz	7000XLI	29.3 Gal/Day	16.2 Gal/Day	325	8.3	20" x 20" x 33.5"	107 lbs	719-2040



INSTANT RESPONSE

Herc Rentals' instant response vehicle is loaded with the right equipment for all of your remediation, restoration, and portable cooling needs. Let us deliver your complete package.

hercrentals.com/remediation

DEHUMIDIFIERS / **DESICCANT**



DRI-EAZ/DriTec 4000i

- 395 CFM
- Runs off (2) 115V plugs - requires separate circuits
- 14 gallons per day at AHAM moisture removal



PHOENIX/D850

- 850 CFM
- 208-240VAC 50/60HZ 1PH in 30A or 50A
- 6" reactivation outlet
- 62 gallons/day at AHAM moisture removal



ARID-DRY/MS-2400

- Variable-frequency drive for CFM control from 1,000 to 2,400 CFM
- Electric reactivation



ARID-DRY/MS-7500

- 5500 - 7500 CFM in one machine
- Allows placement in confined spaces
- 8"-rated extended static pressure
- Compact footprint allows 12 units on standard 53-foot flatbed

MAKE	MODEL	MOISTURE REMOVAL (MAX)	MOISTURE REMOVAL (AT AHAM)	CFM RATING	AMP RATING	DIMENSIONS (LWH)	WEIGHT	CAT-CLASS
Dri-Eaz	DriTec 4000i	N/A	14 Gal/Day	395	12 or 24	20" x 21" x 33"	95 lbs	719-2060
Phoenix	D850	62 Gal/Day	46 Gal/Day	850	30 or 50	23" x 20" x 41"	153 lbs	719-2080
Arid-Dry	MS-2400	230 Gal/Day	158 Gal/Day	2,400	60	92" x 35" x 63"	1,110 lbs	719-1010
Arid-Dry	MS-7500	735 Gal/Day	577 Gal/Day	7,500	179	100" x 50" x 96"	4,400 lbs	719-1030

AIR SCRUBBERS



DRI-EAZ/HEPA 500

- Maintains desired airflow and negative pressure
- Compact design for easy transport
- Daisy chain up to 4 units on (1) 115V 15 Amp outlet

ABATEMENT/BD2KM

- Two speed airflow 1,300 CFM (Low) & 2,000 CFM (High)
- 12 inch exhaust collar
- Visual "Change Filter" indicator lamp

INTERNATIONAL OZONE/TITAN 4000

- Hydroxyl Generator for air purification and deodorizing
- Can treat up to 40,000 cubic feet
- Achieve optimal results by pairing with the Cold Vapor Injector

MAKE	MODEL	MAX CFM	FILTRATION	POWER / AMP RATING	DIMENSIONS	WEIGHT	CAT-CLASS
Dri-Eaz	DefendAir HEPA 500	500	2-Stage	115 V / 3 Amps	18.2" x 26.2" x 24.6"	44 lbs	925-3310
Abatement Technologies	PRED750	750	3-Stage	115V / 1.9 Amps	25.5" x 19.5" x 20.5"	35 lbs	925-3312
Abatement Technologies	BD2KM	2,000	3-Stage	115 V / 10 Amps	39.5" x 28.5" x 31.7"	117 lbs	925-3316
Abatement Technologies	PAS2400	2,100	4-Stage	115 V / 12 Amps	31.5" x 25.3" x 49.8"	170 lbs	925-3318
International Ozone	TITAN 4000	5,000	N/A	115 V / 4 Amps	26" x 26" x 12"	38 lbs	700-1725

AIR MOVERS



DRI-EAZ/ACE TURBODRYER

- Structural drying, carpet and hard floor cleaning, ventilation
- Dry fast with powerful 1881 CFM
- Compact design - stackable for operation

DRI-EAZ/VELO AIRMOVER

- 885 CFM
- Daisy chain up to 6 units per 15 amp circuit for 5,400 CFM
- Low profile with great portability

MAKE	MODEL	CFM	AMPS	DIMENSIONS (LWH)	WEIGHT	CAT-CLASS
Dri-Eaz	Ace TurboDryer	1,881	1.5	19" x 24" x 20.3"	33 lbs	925-3263
Dri-Eaz	Velo Airmover	885	1.9	24" x 9" x 18"	21 lbs	925-3250

SPECIALITY RESTORATION

PACKAGE

NU-ICE AGE/COMMANDO AP

- Environmentally friendly - no chemicals or harmful vapor
- Non-abrasive, nonflammable and nonconductive
- Does not generate any secondary waste
- A 375 CFM air compressor is highly recommended for the Commando AP and required for the Commando 75
- Removes residue, spatter, slag, grease, contaminants, oils, mold and more
- FDA approved method for the food & beverage industry
- A Command Air350 Aftercooler is included in the Blaster rental package



MAKE	MODEL	HOPPER CAPACITY	DRY ICE CONSUMPTION	OPERATING RANGE	BLASTING PRESSURE	DIMENSIONS (LWH)	WEIGHT	CAT-CLASS
NU-ICE AGE	Commando AP	40 lbs	0-425 lbs/hr	60-250 psi @85-185 CFM	60-250 psi	32"x20"x36.3"	168 lbs	100-5150
NU-ICE AGE	Commando 75	75 lbs	0-425 lbs/hr	70-250 psi @ 375 CFM	70-250 psi	35" x 23.3" x 38.8"	225 lbs	100-5155



Includes: Portable Aftercooler/Dryer

NU-ICE AGE/COMMAND AIR350

Every Dry Ice blaster needs an aftercooler to ensure that dry, cool air is flowing into the machine. The COMMAND Air 350 ensures proper intake for your dry ice blaster.

MAKE	MODEL	PRESSURE RATING	FLOW CAPACITY	DIMENSIONS (LWH)	WEIGHT	INLET/OUTLET
NU-ICE AGE	Command Air350	232 psi MAX	233 SCFM @ 100 psi 252 SCFM @ 232 psi MAX	48" x 26.6" x 18.8"	180 lbs	1.5 NPT F in 1" NPT F out



Applications:

- Sanitary cleaning of food processing equipment
- Weld cell cleaning, inc. automation equipment
- Production & packaging equipment
- Ventilation systems
- Automotive parts
- Tire & rubber molds
- Core boxes, aluminum molds
- Commercial printing presses
- Fire & historical restoration
- Mold remediation
- Paper mills and paper related manufacturing
- Electrical and power generation equipment
- Graffiti removal
- Cemeteries & monuments
- Removal of fiberglass resin
- Restaurants & bakeries - grills, ovens, vents
- Dry docking - commercial & military
- Commercial & military aircraft
- Wine barrels
- Asphalt & concrete trucks and equipment